

U.S. DIVISIONAL PATENT APPLICATION

**TACKED COILED FOOD PRODUCTS AND METHOD OF FABRICATING**

DAVID E. BABIARZ  
RONALD T. CAPPADOCIA  
WILLIAM E. LUNDGREN, JR.

Attorney Docket No. 91885/501

Steven J. Goldstein  
Registration No. 28,079  
FROST BROWN TODD LLC  
2200 PNC Center  
201 East Fifth Street  
Cincinnati, Ohio 45202  
(513) 651-6131

"Express Mail"

Mailing Number EK652697314US

Date of Deposit: March 9, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office in Addressee" service under 37 CFR 1.10 and is addressed to The Commissioner of Patents and Trademarks, Washington, D.C. 20231.

KELLY A. KUHL

Print Name

Signature

## TACKED COILED FOOD PRODUCTS AND METHODS OF FABRICATING

### DESCRIPTION

#### Related Applications

This Application claims the benefit of U.S. Provisional Patent Application Serial Number 60/158,456, filed October 8, 1999.

#### Technical Field

5           The present invention generally relates to food items and methods of fabricating, and in particular to the packaging of a food material strip in a manner appealing to consumers.

#### Background of the Invention

10           The merchandising of snack-type food products is a highly competitive business. In addition to the particular type of food material within these products, the novelty and play value are also important factors to consumers when deciding whether to purchase the product.

15           For example, a snack product such as FRUIT ROLL-UPS has found wide market acceptance. This product comprises a dehydrated fruit-based strip of material that must be unrolled and peeled from the packaging. Although dehydrated fruit-based snacks are not new, the process of unrolling and peeling a strip of candy from its packaging is appealing to children and some adults.

#### Summary of the Invention

20           The present invention is a food item and a method of fabricating wherein the food item is packaged in a manner promoting marketability. The food item includes a food material strip or belt having a predetermined length defined by a leading end and a trailing end. The strip is rolled around its leading end into a roll having multiple rotations with an outermost layer in contact with an inner layer. Furthermore, a region of the outermost layer proximate to the trailing end is tacked to the inner layer.

25           The food item can be manufactured by using a fork to coil the strip of food. Then, the outermost layer of the coil proximate to the trailing end of the strip can be tacked to an inner layer of the coiled strip.

### Brief Description of the Drawings

In the accompanying drawings forming part of the specification, and in which like numerals are employed to designate like parts throughout the same,

FIGURE 1 is a perspective view of a food item in accordance with the present invention that has been removed from a bag and includes a tacked coiled strip of food material coated with sugar granules;

FIGURE 2 is a side view of the coiled food item of FIGURE 1;

FIGURE 3 is a top view of an embodiment of a tacking device along with the coiled food item of FIGURE 1 prior to tacking;

FIGURE 4 is a cross sectional view of the food item shown in FIGURE 3 taken along plane 4-4;

FIGURE 5 is similar to FIGURE 4, but with the tacking device injected into the coiled food item;

FIGURE 6 is similar to FIGURE 5, but with the tacking device withdrawn from the coiled food item;

FIGURE 7 is a table listing the preferred ingredients of the food material of FIGURE 1;

FIGURE 8 is a schematic view of a fabrication system having a plurality of mechanisms for coiling and tacking strips of food material in accordance with the present invention;

FIGURE 9 is an elevated view of one of the coiling and tacking mechanisms of FIGURE 8, before receiving a strip of food material, and having a fork, a tacking device and a sensor device;

FIGURE 10 is a perspective view of the tacking device associated with the coiling and tacking mechanism of FIGURE 9;

FIGURE 11 is a perspective view of the coiling and tacking mechanism of FIGURE 9;

FIGURE 12 is an elevated view of the mechanism of FIGURE 9 receiving a strip of food material;

FIGURE 13 is an elevated view of the mechanism of FIGURE 12 after coiling the strip of food material;

5        FIGURE 14 is an elevated view of the mechanism of FIGURE 13, but with the prongs of the tacking device injected into the coiled strip of food material;

FIGURE 15 is a perspective view of the mechanism of FIGURE 14, but with the tacked coiled strip of food released from the mechanism; and,

10        FIGURE 16 is a partial plan view of the mechanism of FIGURE 15 depicting the fork in the retracted, second position, to release the tacked coiled strip of food.

#### Detailed Description

15        While this invention is susceptible of embodiments in many different forms, there is shown in the drawings and will herein be described in detail a preferred embodiment of the invention with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the broad aspect of the invention to the embodiments illustrated.

20        Referring to FIGURES 1-2, a food item 10 in accordance with the present invention is depicted comprising a tacked coiled belt or strip 12 of food material 14 sanded or coated with sugar granules. The food strip 12 consists of candy or a like food substance such as a sour flavored food material comprising the ingredients shown in FIGURE 7.

25        The food strip has two planar side surfaces 18, 20, a leading end 22, an opposite trailing end 24, and two parallel edges 26, 28 extending longitudinally. The length of the food strip 12 extends from the strip's leading end 22 to its trailing end 24. The width of the food strip 12 extends between the strip's parallel edges 26 and 28.

The strip of food material 12 is sanded or coated on both side surfaces 18, 20 with sugar or the like. The strip 12 is coiled multiple times around the leading end 22 to define a plurality of loops or layers in overlapping relationship. Each loop or layer

has a side surface in contact with, and thus supported by, another side surface of the strip of food material 12.

In an embodiment, an end portion or region 36 of the strip 12 proximate to the trailing end 24 is attached by tacking to an inner layer of the strip to prevent uncoiling of the food item. Moreover, the coiled food item 10 can be enclosed within a sealed plastic bag 38 or the like to preserve the freshness of the food material.

Turning to FIGURES 3-6, an embodiment of a method for fabricating a food item 10 in accordance with the present invention is depicted. As shown in FIGURES 3 and 4, prior to tacking the coiled strip 12 of food material 14, a tacking device 40 is provided having, in an embodiment, a heating element 42 and a pair of prongs or needles 44 and 46. The heating element 42 heats the needles 44, 46 to a predetermined temperature of, preferably, about 160 degrees Fahrenheit. The needles 44, 46 are injected into the coiled strip 12 such that the needles 44, 46 penetrate the outermost layer 48 of the coil and also penetrate into an inner layer 50 adjoining the outermost layer as shown in FIGURE 5.

The heating of the food material 14 about the needles 44, 46 tacks the associated portion 38 of the outermost layer 48 to the inner adjoining layer 50 of the coiled strip 12. Then, the needles 44, 46 are removed as shown in FIGURE 6 and the coiled strip 12 can, if desired, be deposited into a bag 38 or the like.

In an alternative embodiment, the needles 44, 46 can be injected through multiple layers of the coiled strip 12. Further, only one needle can be used for tacking the coiled strip 12, or if desired, more than two needles.

Turning back to FIGURES 1-2, in another embodiment, the region 36 of the strip 12 proximate to the trailing end 24 is tacked or welded to the inner layer 50 of the strip 12 by pressing portions of the outermost layer 48 against portions of the inner layer. In this alternative embodiment, no heat is used to tack the layers together.

FIGURE 8 provides a schematic view of a fabrication system 52 having a plurality of mechanisms 80 for coiling and then tacking strips of food material by

pressing portions of two layers together. The system 52 includes an extrusion head 56 for forming a plurality of spaced, parallel, narrow strips 12 of food material 14. The extrusion head 52 receives food material that is heated to an amorphous state allowing for even extrusion of the strips 12 of food material onto an endless conveyor belt 58.

The strips 12 of food material 14 are directed through a bath 60 of edible oil 62 and onto another endless conveyor belt 64 extending through a cooling tunnel 66. The oil, such as CAPOL or the like, preferably consists of a curing agent to keep acid in the strips 12. The temperature of the food material 14 is lowered as it passes through the cooling tunnel 66 for converting the food material 14 from an amorphous state to a pliable solid.

The strips 12 of food material exiting the cooling tunnel 66 are next directed onto an endless stainless steel wire mesh conveyor belt 68. The conveyor belt 68 extends through a conventional device, known in the art as a sander 70, for evenly spreading and pressing granules of sugar onto the strips 12. This process, known in the art as sanding, attaches the sugar granules to the outer surface of the strips 12.

The strips 12 of food material exiting the sander 70 are passed onto an inclined endless conveyor belt 72 for transporting the strips onto an elevated conveyor system 74 consisting of a plurality of elevated conveyors 76 separated from each other by a plurality of divides 78. Mounted below the elevated conveyor system 74 are a plurality of mechanisms or stations 80 for individually coiling and tacking the strips 12 of food material as explained in detail further herein.

As shown in FIGURE 8, each strip 12 of food material is transferred from the elevated conveyor system 74 onto a respective inclined endless conveyor belt 82 wherein the strip is cut by a knife 84 to define the trailing or cut end 24 of the strip. The leading end 22 of each strip 12 is received between first and second spaced parallel legs or tines 86, 87 of a fork 88 associated with a corresponding coiling and tacking mechanism 80. The legs 86, 87 of each fork 88 preferably have a length at least equal to the transverse width of an individual strip 12 of food material 14.

Turning to FIGURES 9 and 11, the fork 88 of each coiling and tacking mechanism 80 is operably connected, via a shielded drive coupling 91, to a motor 90 for rotating the fork 88 about an axis located parallel to the legs 86, 87. Fork 88 is reciprocated between a first, engaged or extended position (FIGURES 9, 11-14) extending generally in line with the path of the strip 12 exiting the associated inclined conveyor belt 82 (FIGURE 8), and a second, disengaged or retracted position (FIGURES 15 and 16) located to one side of the inclined conveyor 82 and transversely spaced from the first, engaged position. Preferably, fork 88 is reciprocated from the first and second positions, and vice versa, by a double-action pneumatic cylinder 92.

Each coiling and tacking mechanism 80 includes a pressure application device 94 for maintaining pressure against the food strip 12 as the strip is being coiled. Accordingly, the strip 12 is prevented from uncoiling by the pressure application device 94 before, and while, the coiled strip is being tacked. The pressure application device 94 preferably consists of a metal or metal alloy beam 96 having an arcuate end 98 and a bias member attachment end 100. The pressure application device 94 is pivotally coupled to a fixed intermediate member 102 to allow the beam 96 to pivot about the fixed member 102. The attachment end 100 of the beam 96 is coupled to a spring-load 104 comprising a spring 106 mounted about a shaft 108 having a distal end cap 109 attached thereto and in abutting relationship to the spring.

The arcuate end 98 of the pressure application device 94 reciprocates between a first inner position (FIGURES 9 and 12), wherein the arcuate end 98 is radially spaced by a predetermined distance "d" from the fork 88 in its extended position, and a second outer position (FIGURES 13 and 14), wherein the arcuate end 98 is radially spaced from the fork in its extended position by a distance greater than "d."

The arcuate end 98 of the pressure application device 94 is pressed against the food strip 12 by the spring-load 104 during at least a portion of the coiling of the food strip. Accordingly, the arcuate end 98 of the pressure application device 94 is moved from the first inner position (FIGURE 9) to the second outer position (FIGURES 13 and

14) as the outer diameter of the coiled food strip 12 increases in outer diameter size during the coiling process. Correspondingly, once the coiled food item is removed from the fork 88, the arcuate end 98 of the pressure application device 94 moves from the second outer position to the first inner position by the force applied by the spring-load 104 to the bias attachment end 100 of the pressure application device.

Turning to FIGURE 12, in operation, the leading end 22 of a food strip 12 is fed by the inclined conveyor belt 82 (FIGURE 8) between the legs 86, 87 of the fork 88 while the fork is positioned in its first engaged position and being stationary with the legs located to allow the leading end 22 of the food item to be fed therebetween. Preferably, a sensor device 133 is provided for detecting when the leading end 22 of the food strip 22 has been fed between the legs 86,87 of the fork 88. In an embodiment, the sensor device 133 is a conventional laser sensor that emits a laser beam 137. When the strip 22 is fed between the fork legs 86,87, the laser beam 137 reflects off the strip and back to the sensor. The sensor detects the reflection and, as a result, provides for enabling the motor 90 to rotate the fork 88 about an axis parallel with the legs 86, 87.

With reference to FIGURE 12, the fork 88 is preferably rotated in a clockwise direction as shown by arrow "A." As the fork 88 is rotated, it can be appreciated that the strip 12 of food 14 is rolled into a coil around its leading end 22 on, and around, the legs 86, 87 of the fork as shown in FIGURE 13. In an embodiment, the motor 90 can rotate the fork 88 at adjustable speeds such that rotation of the fork is gradually decreased once the food strip 12 begins coiling about the fork. Likewise, if desired, the speed of conveyor belt 82 can be increased as the food strip coils about the fork 88.

Also, as the strip 12 of food 14 is rolled, the coil comes into contact against the pressure device's arcuate end 98 in its first, inner position. In its first inner position, the pressure device's arcuate end 98 places pressure on the rolling, coiled-up strip of food. Thus, the fork 88 acts as a rotating anvil, and with the pressure member's arcuate end 98, sandwiches the coiled-up strip of food therebetween.



Turning to FIGURE 14, after the fork 88 has rotated the desired amount of times to completely coil the strip 12 of food 14, rotation of the fork is slowed to a complete stop. At that time, a tacking device 140 having a pair of prongs 144 and 146 (FIGURE 10) maintained in spaced parallel relationship to each other are injected into the coiled strip 12. The prongs 144, 146 are connected to a double-action pneumatic cylinder 123 for injecting and, if desired, retracting the tips of the prongs 144, 146 from the coiled strip 12. Preferably, the prongs 144, 146 are a pair of spaced coplanar elongated strips fabricated of a metal or metal alloy with each prong having a tip 153 for injecting into the coiled food strip 12.

In an embodiment, the tips 153 of the prongs 144, 146 are injected into the outermost layer 48 of the coil to penetrate into the layer 50 adjoining the outermost layer. As the prongs 144, 146 are injected into the coil, a portion of the pressure application device's arcuate end 98 is positioned between the prongs while maintaining pressure against the coil to keep the coil from unraveling. Preferably, the terminal distal ends 173 of the prongs 144, 146 are blunted so that, by being injected into the coiled strip, the outer outermost layer 48 of the coil is pressed into, and thus becomes tacked to, the inner adjoining layer 50 of the coil.

After the coiled strip 12 has been tacked, the fork 88 is axially slid from the coiled food item 10 by reciprocating the fork transversely from its first, engaged position shown in FIGURES 9 and 11-14 to its second, disengaged position shown in FIGURES 15 and 16. The fork 88 is reciprocated by cylinder 92, with the individual tacked coiled strip of food 14 falling from the fork 88 as it is retracted. In an embodiment, the tacked coil of food falls onto a suitable collector means or removal conveyor, not shown.

As shown in FIGURE 16, the legs 86, 87 of the fork 88 are retracted through a corresponding pair of apertures 183 in a rotatable stationarily mounted disk 185, with the coiled strip of food abutting the disk and axially sliding from the fork as the fork is transversely reciprocated into the apertures. After the fork 88 has reciprocated to its second, disengaged position as shown in FIGURES 15 and 16, so the coiled strip 12 of

food 14 falls therefrom, the fork is moved back to its first, engaging position of FIGURE 12 by cylinder 92, wherein legs 86 and 87 are positioned to accept the leading end of the next strip 12 of food 14. Before the next strip of food is coiled, prongs 144, 146 are retracted away from fork 88 by double-action pneumatic cylinder 123.

5           While the specific embodiments have been illustrated and described, numerous modifications come to mind without significantly departing from the spirit of the invention and the scope of protection is only limited by the scope of the accompanying Claims.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000